

TABLE I

*Amplitude/frequency response of the recorded short-circuit flux
in decibels*

Recorded level relative to level at 315 Hz			Frequency in hertz	Recorded level relative to level at 1 000 Hz				
Time constants in microseconds				Time constants in microseconds				
$t_1 + t_2$ 70 + 3 180	$t_1 + t_2$ 90 + 3 180	$t_1 + t_2$ 120 + 3 180		$t_1 = 17.5$	$t_1 = 35$	$t_1 = 50$	$t_1 + t_2$ 50 + 3 180	$t_1 = 70$
+10.3	+10.4	+10.5	16	+0.1	+0.2	+0.4	+10.7	+0.8
+8.6	+8.6	+8.7	20	+0.1	+0.2	+0.4	+9.0	+0.8
+7.0	+7.0	+7.1	25	+0.1	+0.2	+0.4	+7.4	+0.8
+5.4	+5.5	+5.6	31.5	+0.1	+0.2	+0.4	+5.9	+0.8
+4.1	+4.1	+4.2	40	+0.1	+0.2	+0.4	+4.5	+0.8
+3.0	+3.0	+3.1	50	+0.1	+0.2	+0.4	+3.4	+0.8
+2.1	+2.1	+2.2	63	+0.1	+0.2	+0.4	+2.5	+0.8
+1.4	+1.5	+1.5	80	+0.1	+0.2	+0.4	+1.8	+0.8
+0.9	+1.0	+1.1	100	+0.1	+0.2	+0.4	+1.4	+0.8
+0.6	+0.7	+0.7	125	+0.1	+0.2	+0.4	+1.0	+0.8
+0.4	+0.4	+0.5	160	+0.1	+0.2	+0.4	+0.8	+0.7
+0.2	+0.2	+0.3	200	+0.1	+0.2	+0.4	+0.6	+0.7
+0.1	+0.1	+0.1	250	0	+0.2	+0.4	+0.5	+0.7
0	0	0	315	0	+0.2	+0.4	+0.5	+0.7
-0.1	-0.1	-0.2	400	0	+0.2	+0.3	+0.4	+0.6
-0.2	-0.3	-0.4	500	0	+0.2	+0.3	+0.3	+0.6
-0.3	-0.5	-0.7	630	0	+0.1	+0.2	+0.3	+0.4
-0.5	-0.8	-1.2	800	0	+0.1	+0.1	+0.1	+0.3
-0.8	-1.2	-1.8	1 000	0	0	0	0	0
-1.2	-1.7	-2.6	1 250	0	-0.1	-0.2	-0.2	-0.4
-1.8	-2.6	-3.8	1 600	-0.1	-0.3	-0.6	-0.6	-1.0
-2.5	-3.5	-5.0	2 000	-0.2	-0.6	-1.0	-1.0	-1.7
-3.5	-4.7	-6.5	2 500	-0.3	-0.9	-1.7	-1.7	-2.7
-4.7	-6.2	-8.1	3 150	-0.4	-1.5	-2.6	-2.6	-3.9
-6.1	-7.8	-9.9	4 000	-0.7	-2.3	-3.7	-3.7	-5.4
-7.7	-9.5	-11.7	5 000	-1.1	-3.2	-5.0	-5.0	-6.9
-9.4	-11.3	-13.6	6 300	-1.7	-4.5	-6.5	-6.5	-8.6
-11.3	-13.3	-15.6	8 000	-2.4	-5.9	-8.2	-8.2	-10.5
-13.1	-15.2	-17.5	10 000	-3.4	-7.5	-10.0	-10.0	-12.3
-15.0	-17.0	-19.4	12 500	-4.6	-9.1	-11.7	-11.8	-14.2
-17.1	-19.2	-21.5	16 000	-6.1	-11.1	-13.8	-13.8	-16.3
-19.0	-21.1	-23.5	20 000	-7.6	-12.9	-15.7	-15.7	-18.2

Note. - A correction factor has been applied to obtain zero reference at 315 Hz and 1 000 Hz as specified for calibration tapes according to IEC Publication 94-2.